

Major Specifications All-new Swift Sport

Number of doors			5-door
Engine			Petrol
			1.4 BOOSTERJET
Drive system			2WD
DIMENSIONS			
Overall length		mm	3.890
Overall width		mm	1.735
Overall height		mm	1.495
Wheelbase		mm	2.450
Tread	Front	mm	1.510
	Rear	mm	1.515
Minimum turning radius *		m	5,1
Minimum ground clearance		mm	120
CAPACITIES			
Seating capacity		persons	5
Fuel tank capacity		litres	37
Luggage capacity *	Max. volume (fixed rear seat)		
	- with emergency flat tyre repair kit	litres	947
	Rear seatback folded (VDA method)		
	- with emergency flat tyre repair kit	litres	579
	Rear seatback raised (VDA method)		
	- with emergency flat tyre repair kit	litres	265
ENGINE			
Type			K14C
Number of cylinders			4
Number of valves			16
Piston displacement		cm3	1.373
Bore x stroke		mm	73.0 x 82.0
Compression ratio			9,9
Maximum output		kW/rpm	103/5,500
Maximum torque		N·m/rpm	230/2,500-3,500
Fuel distribution			Direct injection
TRANSMISSION			
Type			6MT
Gear ratio	1st		3,615
	2nd		1,954
	3rd		1,275
	4th		0,942
	5th		0,794
	6th		0,674
	Reverse		3,481
Final gear ratio			3,944
CHASSIS			
Steering			Rack & Pinion
Brakes	Front		Ventilated disc
	Rear		Disc
Suspension	Front		MacPherson strut with coil spring
	Rear		Torsion beam with coil spring
Tyres			195/45R17 81W
Nominal rim diameter			17 x 6 1/2J
WEIGHTS			
Kerb weight (min./with full option)		kg	975 (with Start stop system)
Gross vehicle weight		kg	1.445
PERFORMANCE			
Maximum speed *1		km/h	210
0-100 km/h *		sec	8,1
ENVIRONMENTAL PERFORMANCE			
Emission standard compliance			Euro 6
Fuel consumption (NEDC)*2	Urban	litres/100km	6,8
	with Engine Auto Stop Start system	litres/100km	4,8
		litres/100km	5,6
CO2 emissions (NEDC)*2	with Engine Auto Stop Start system	g/km	125
CO2 emissions (WLTP)*3	with Engine Auto Stop Start system	g/km	135

Specifications may vary for individual markets.

\*1 Manufacture data

\*2 NEW European Driving Cycle

\*3 Worldwide Harmonized Light-duty vehicles Test Procedures